



AlphaPlus® C₃₀₊ Sales Specifications

Characteristics	Method	Unit	Specification	
			Min	Max
<C ₂₂	GLC	wt. %	-	0.10
C ₂₂	GLC	wt. %	-	1.00
C ₂₄ -C ₂₈	GLC	wt. %	-	18.0
C ₃₀₊	GLC	wt. %	82.0	-
Kinematic Viscosity @ 210 °F	ASTM D 445	cSt	-	10.0
Color (Unfiltered)	ASTM D 6045	Saybolt	0	-
Appearance **	ASTM D 4176	-	Pass	-
API Gravity @ 60°F *	ASTM D 287	-	-	-
Specific Gravity @ 60°F/ 60°F *	ASTM D 287	-	-	-
Dropping Point *	ASTM D 3954	°F	164	-

* Determine and Report

** Clear and substantially free of visual impurities

Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. Qatar Chemical Company II Ltd. does not make, and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, tort or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as any international laws which may be encountered in the use thereof. Such questions should be investigated by the user.

For more information:

Qatar Chemical Company II Ltd.
(Q-Chem II)
P.O. Box 24646
Doha, Qatar
Tel: (+974) 4484-7110
(+974) 4484-7111
email: marketing@qchem.com.qa
MSDS (+974) 4484-7110
OR
visit our site
www.qchem.com.qa